

X10c

The professional for hot and cold speciality coffees – versatile, robust and reliable.





Benefits at a glance

- 34 speciality coffees from espressi and cappuccini to Cold Brew
- Robust and sophisticated
- The design is characterised by clean lines and maximum functionality
- Supports modern payment systems
- Flexible mains water connection for direct water supply as well as occasional stand-alone use

Recommended accessories

- Business Connect
- JURA Pocket Pilot 3.0
- Wi-Fi Connect V2
- MDB Connect
- MDB Interface 2.0
- Cubwarmer
- Accessory set for HPX3 milk systems
- Cool Control 2.51
- Bean container extension
- Coffee grounds disposal/ drip drain set

Areas of use

- Self-service areas
- Large offices
- Canteens
- Care facilities

Recommended maximum daily output 100 cups

The X10c sets new standards and brings variety and freshness to the professional environment. Quite literally, because its repertoire proudly includes 34 speciality coffees, eight of which are cold-extracted. In addition to the classic Hot Brews and the popular Cold Brews, the professional automatic coffee machine also offers a variety of americanos and lungos. With the One-Touch Lungo function, the professional also prepares the extended specialities at the touch of a button. The P.A.G.2+ grinder, user-friendliness and functionality of the X10c are impressive: the colour display and physical buttons make interacting with the automatic coffee machine intuitive and inviting. The X10c is the perfect size for use in offices and self-service areas with a daily requirement of 100 coffee preparations. The permanent water connection offers the convenience of a constant supply of fresh water. Thanks to the flexible connection solution, the X10c can be easily disconnected from the water connection, making it ideal for occasional standalone use. "Form follows function" is the maxim of the design concept. From the clear lines to the practical dual spout and the MDB interface – the professional fully automatic coffee machine is impressive in every respect.





X10c

Technical overview

Specific advantages	
Number of specialities	34
Cold Extraction Process	•
Intelligent preheating	
3D brewing technology	•
Active bean monitoring	•
Automatic switchover from milk to milk foam	•
WiFi connection to home network	•
JURA coffee machine standards	
Pulse Extraction Process (P.E.P.®)	
One-Touch Lungo function	
One-Touch-function	
Variable brewing unit	5 – 16 g
Grinder	P.A.G.2+
High-performance pump, 15 bar	1
Thermoblock heating system	1
Fluid systems	1
Milk system/interchangeable milk spout	HP3/CX2
Operating and programming standards	
Compatible with Payment Connect	•
Compatible with MDB Connect	
Compatible with Wi-Fi Connect V2	
Compatible with Business Connect	2.5" 1.
Display	3,5" colour display with buttons
Programmable amount of water for coffee	•
Programmable coffee strength	10 levels
Programmable amount of milk/milk foam	•
Programmable milk/milk foam temperature	3 levels
Programmable brewing temperature	3 levels
Programmable hot water temperature	3 levels
Resettable day counter	•
Shows the number of preparations for each individual product	

Intelligent Water System (I.W.S.)	
Filter cartridge	CLARIS Pro Smart maxi / CLARIS Pro Smart+
One-Touch milk system cleaning (automatic)	
Integrated rinsing, cleaning	
and descaling programme	
Monitored drip tray	•
Bean container and water tank can be locked	
JURA hygiene: TÜV-certified	•
Energy standards	
Energy Save Mode (E.S.M.®)	
Zero-Energy Switch or power switch	•
Programmable switch-off time	•
Design and materials	
Design and materials Amber/white cup illumination	
Amber/white cup illumination	63 – 150 mm
Amber/white cup illumination In figures Height-adjustable dual spout with hot-water spout	63 – 150 mm 2,8 l
Amber / white cup illumination In figures Height-adjustable dual spout with hot-water spout Water tank capacity	
Amber/white cup illumination In figures Height-adjustable dual spout with hot-water spout	2,81
Amber/white cup illumination In figures Height-adjustable dual spout with hot-water spout Water tank capacity Bean container holding capacity	2,8 l 500 g
Amber/white cup illumination In figures Height-adjustable dual spout with hot-water spout Water tank capacity Bean container holding capacity Bean container can be optionally extended to Coffee grounds container (servings)	2,8 l 500 g 1 kg
Amber/white cup illumination In figures Height-adjustable dual spout with hot-water spout Water tank capacity Bean container holding capacity Bean container can be optionally extended to	2,81 500 g 1 kg max. 40
Amber/white cup illumination In figures Height-adjustable dual spout with hot-water spout Water tank capacity Bean container holding capacity Bean container can be optionally extended to Coffee grounds container (servings) Cable length	2,8 l 500 g 1 kg max. 40 ca. 1,2 m
Amber/white cup illumination In figures Height-adjustable dual spout with hot-water spout Water tank capacity Bean container holding capacity Bean container can be optionally extended to Coffee grounds container (servings) Cable length Voltage/Power	2,8 I 500 g 1 kg max. 40 ca. 1,2 m 230 V~/1450 W
Amber/white cup illumination In figures Height-adjustable dual spout with hot-water spout Water tank capacity Bean container holding capacity Bean container can be optionally extended to Coffee grounds container (servings) Cable length Voltage/Power Current Mains water connection thread size	2,8 l 500 g 1 kg max. 40 ca. 1,2 m 230 V~/1450 W
Amber / white cup illumination In figures Height-adjustable dual spout with hot-water spout Water tank capacity Bean container holding capacity Bean container can be optionally extended to Coffee grounds container (servings) Cable length Voltage / Power Current Mains water connection thread size Stand-by power	2,8 I 500 g 1 kg max. 40 ca. 1,2 m 230 V~/1450 W 10 A G 3/8" < 0,5 W
Amber/white cup illumination In figures Height-adjustable dual spout with hot-water spout Water tank capacity Bean container holding capacity Bean container can be optionally extended to Coffee grounds container (servings) Cable length Voltage/Power Current Mains water connection thread size Stand-by power Weight	2,8 I 500 g 1 kg max. 40 ca. 1,2 m 230 V~/1450 W 10 A G 3/8" < 0,5 W 13,2 kg
Amber / white cup illumination In figures Height-adjustable dual spout with hot-water spout Water tank capacity Bean container holding capacity Bean container can be optionally extended to Coffee grounds container (servings) Cable length Voltage / Power Current Mains water connection thread size Stand-by power	2,8 I 500 g 1 kg max. 40 ca. 1,2 m 230 V~/1450 W 10 A G 3/8" < 0,5 W



Hygiene standards



www.tuv.com ID 0000027526